

140BBL ULTRA-LITE VACUUM TRAILER

TYPE: Non-Code Vacuum Trailer

- CAPACITY: 5880 US Gallons +- 3%
- COMMODITIES: Unspecified Oilfield Fluids
- SHELL: 3/16" A36 Carbon Steel, Single Compartment
- HEADS: ¼" A36 Carbon Steel, Flanged & Dished
- BAFFLES: (2) ¼" A36 Carbon Steel, Flanged & Dished
- STIFFENING RINGS: (8) 3/8" X 2-1/2" A36 Carbon Steel Flat Bar Rings MANWAYS: (3) 20" Hinged Manways with Domed Lids on Top and
- (1) On Rear Head
- FRAME: ¼" A36 Carbon Steel, Full Length of Tank
- HOSE TRAYS: 20' Aluminum on Both Sides with Drain at Rear.
- BUMPER: Combination Rear Step with Heavy Duty Pull Eye
- LADDER: Ladder with Platform on LH Side Aligned with Center Manway
- VACUUM KITS: Front Manway Fitted with Primary Shutoff and (1) 12" OD, 10 Gallon Secondary Shutoff on LH Side with Liquid Filled Vacuum/ Pressure Gauge
- RELIEFS: (1) 2" Vacuum Relief Valve and (1) 2" Pressure Relief Valve on Top of Tank

- LEVEL GAUGE: (1) 2" Sight Glass Mounted On Rear Head with Brass Ball Valves on Top & Bottom for Isolating Sight Glass
- MUD FLAPS: Standard Rubber
- TOOL BOX: (1) 18" X 18" X 36" Aluminum Tool Box with Drip Rail, Bolted to Heavy Duty Brackets
- LANDING GEAR: Heavy Duty Two-Speed with Sand Shoes
- AXLES: (2) 25,000lb Axles
- SUSPENSION: Hutch CH9700, 8-Leaf, 4-Spring Suspension, Flange Mounted with Heavy Duty Cast Brackets
- BRAKES: 16-1/2" X 7" S-Cam Type with Automatic Slack Adjusters and 30/30 Spring Brake Chambers. Premium Sealco Anti-Lock Brake System on Both Axles
- TIRES: 11R24.5 Radial Tires with Chip Resistant Compound
- WHEELS: Steel, 10-Hole Hub Piloted Tubeless Disc Wheels, Painted White
- LIGHTING: 100% Sealed Light Wiring Harness System with Sealed LED Lights to Comply with FMVSS. Strobe Light Mounted on the Rear. (2) Work Lights Mounted on the Rear
- PAINT: Sandblast, Prime and Paint One Standard Solid Color Using High Quality Urethane Paint

Many Custom Options Available. Call For More Information.

*Photo may show additional options

