

TROXELL TRAILER MFG.



150BBL ULTRA-LITE VACUUM TRAILER

TYPE: Non-Code Vacuum Trailer

CAPACITY: 6300 US Gallons +- 3%

COMMODITIES: Unspecified Oilfield Fluids

SHELL: 3/16" A36 Carbon Steel, Single Compartment

HEADS: 1/4" A36 Carbon Steel, Flanged & Dished

BAFFLES: (2) 1/4" A36 Carbon Steel, Flanged & Dished

STIFFENING RINGS: (8) 3/8" X 2-1/2" A36 Carbon Steel Flat Bar Rings

MANWAYS: (3) 20" Hinged Manways with Domed Lids on Top and

(1) On Rear Head

FRAME: 1/4" A36 Carbon Steel, Full Length of Tank

HOSE TRAYS: 20' Aluminum on Both Sides with Drain at Rear.

BUMPER: Combination Rear Step with Heavy Duty Pull Eye

LADDER: Ladder with Platform on LH Side Aligned with Center Manway

VACUUM KITS: Front Manway Fitted with Primary Shutoff and (1) 12" OD,

10 Gallon Secondary Shutoff on LH Side with Liquid Filled Vacuum/
Pressure Gauge

RELIEFS: (1) 2" Vacuum Relief Valve and (1) 2" Pressure Relief Valve on

Top of Tank

LEVEL GAUGE: (1) 2" Sight Glass Mounted On Rear Head with Brass Ball
Valves on Top & Bottom for Isolating Sight Glass

MUD FLAPS: Standard Rubber

TOOL BOX: (1) 18" X 18" X 36" Aluminum Tool Box with Drip Rail, Bolted to Heavy
Duty Brackets

LANDING GEAR: Heavy Duty Two-Speed with Sand Shoes

AXLES: (2) 25,000lb Axles

SUSPENSION: Hutch CH9700, 8-Leaf, 4-Spring Suspension, Flange Mounted with
Heavy Duty Cast Brackets

BRAKES: 16-1/2" X 7" S-Cam Type with Automatic Slack Adjusters and 30/30 Spring
Brake Chambers. Premium Sealco Anti-Lock Brake System on Both Axles

TIRES: 11R24.5 Radial Tires with Chip Resistant Compound

WHEELS: Steel, 10-Hole Hub Piloted Tubeless Disc Wheels, Painted White

LIGHTING: 100% Sealed Light Wiring Harness System with Sealed LED

Lights to Comply with FMVSS. Strobe Light Mounted on the Rear.

(2) Work Lights Mounted on the Rear

PAINT: Sandblast, Prime and Paint One Standard Solid Color Using High Quality
Urethane Paint

Many Custom Options Available. Call For More Information.

*Photo may show additional options

TroxellTrailer.com
For Sales Call 817.223.7309